



WING PRO

INDUSTRIAL AIR CURTIAN



AIR CURTAINS
FOR PROFESSIONALS

Technical parameters

PARAMETERS	WING PRO DOUBLE ROW COIL				WING PRO SINGLE ROW COIL				WITHOUT HEATING (AMBIENT)				
	W150		W200		W150		W200		C150		C200		
	AC	EC	AC	EC	AC	EC	AC	EC	AC	EC	AC	EC	
VTS article No.	1-4-2801-0346	1-4-2801-0349	1-4-2801-0352	1-4-2801-0355	1-4-2801-0345	1-4-2801-0348	1-4-2801-0351	1-4-2801-0354	1-4-2801-0344	1-4-2801-0347	1-4-2801-0350	1-4-2801-0353	
Max. height of door	m	1,5	2		1,5	2		1,5		2			
Max. air stream range	m	7		7,5		8							
Max. flow rate	m³/h	7 300	10 700		7 900	11 900		8 500	12 800				
Heating power range	kW	17-58	28-88		3-32	15-48							
Max. temperature of heating medium	°C	130											
Max. Working pressure	MPa	1,6											
Diameter of stub pipe connectors	"	3/4											
Supply voltage	V/ph/Hz	~230/1/50											
AC motor power	kW	2 x 0,28	3 x 0,28		2 x 0,28	3 x 0,28		2 x 0,28	3 x 0,28				
Rated current (AC motor)	A	2 x 1,3	3 x 1,3		2 x 1,3	3 x 1,3		2 x 1,3	3 x 1,3				
EC motor power	kW	2 x 0,25	3 x 0,25		2 x 0,25	3 x 0,25		2 x 0,25	3 x 0,25				
Rated current (EC motor)	A	2 x 1,3	3 x 1,3		2 x 1,3	3 x 1,3		2 x 1,3	3 x 1,3				
Weight AC/EC (without water)	kg	52,9	53,6	67,4	69,6	47,5	50,5	64	66,1	42,7	43,4	56,2	58,3
IP protection rating	IP	54											



Accessories



HMI WING EC controller



Wall controller WING/VOLCANO



Door sensor (reed switch)



Valve with actuator



Flex. connection hoses (set)

VTS article No.	1-4-2801-0155	VTS article No.	1-4-0101-0438	VTS article No.	1-4-0101-0454	VTS article No.	1-2-1204-2019	VTS article No.	1-2-2702-0076
Motor support	- EC	Motor support	- AC	Contact configuration	- NO	Power supply voltage	V/ph/Hz ~230/1/50	Length	m 0,6-0,9
Power supply voltage	V/ph/Hz ~230/1/50	Power supply voltage	V/ph/Hz 6(3)	Switching current	mA 500	Opening	min 3/3	Connection type	GW 3/4"
Permissible load	A 1A for 230VAC 0,02A for 0-10V	Permissible load	A 1A for 230VAC 0,02A for 0-10V	Switching voltage	V max 200 V	Kvs	- 4,5	Max. fluid pressure	MPa 1,6
Setting range	°C 5...40	Setting range	°C 10...30	Connection	°C screw	Protection rating	IP 54	Min. working temperature for water	°C 5
Protection rating	IP 20	Protection rating	IP 30					Min. working temperature for glycol	°C -20
								Max. working temperature	°C 130
								Set includes	- hose (2 pcs) gasket (4 pcs)

Noise level

Fan speed	Noise level	WING PRO W R1		WING PRO W R2		WING PRO C	
		1,5m	2m	1,5m	2m	1,5m	2m
I	dB(A)*	45	46	45	45	47	48
II		55	57	54	55	57	58
III		64	65	62	63	65	66

* speed measurement conditions: semi-open space, horizontal installation on the wall, measurement performed 5 m away from the device